



Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899 Fax: (852) 2121-8898

E-mail: enquiry@vcast.net
Homepage: http://www.vcast.net

### **Mandatory Requirements**

### VCAST All-In-One Server 4010ER (VC-SR4010ER)

#### **General Features:**

- Support high-quality video/audio broadcast at various bit-rates for multiple devices (PC, TV via VBOX or Windows Mobile)
- Support live and on-demand video / audio broadcasting via any TCP/IP networks
- Support ease-of-use web-based user interface for centralized content management
- Highly scalable and expandable from small to large scale of streaming
- Ease of support and maintenance with remote management
- Support latest streaming technologies for best user experience over Internet, Intranet or Wireless
- Reliable for 7/24 operation with high availability and backup options
- Support publishing, re-broadcasting and content delivery via Vcast Network for global broadcasting (optional at charge-basis)
- Provided by Certified Windows Media Hardware Product Vendor (Integrated Capture/Encoding Solutions and Appliances) listed in
  - http://www.microsoft.com/windows/windowsmedia/service provider/Hardware/default.aspx#capture
- Provided by Certified Windows Media Software Product Vendor (Software/Content Management) listed in
  - http://www.microsoft.com/windows/windowsmedia/service provider/Software/default.aspx#content

### **Encoding Features:**

- Professional turnkey streaming video encoder with video/audio inputs and streaming outputs
- Support real-time encoding in multiple bit-rates for each channel
- Support professional quality of audio and video encoding from live input(s) and transcoding from archived media files
- Support conventional and professional audio and video interfaces (e.g. S-video, Composite Video, Aux, Line, Mic mini-jack audio)
- Fully synchronized audio and video streaming
- Elastic Frame Buffer architecture for absolute reliability and high image quality
- Integrated professional video and audio processing (e.g. high performance scalars, audio processor, video processor, AV matrix switch, etc)

#### **Streaming Features:**

- Support and compatible with Windows Media 6, 7, 8, 9, SMPTE VC-1, MP3 formats
- Support unlimited\* no. of broadcasting channels
- Support "Fast Streaming" capabilities which can effectively eliminate buffering time, and reduce the
  playback interruptions due to network conditions. Features like Fast Start, Fast Cache, Fast Recovery,
  and Fast Reconnect provide an always-on viewing experience by streaming content with minimal
  buffering and down-time, even over high latency network connections such as wireless and satellite.
- Support instant-on/always-on playback which can dramatically improves streaming reliability, responsiveness user experience and virtually eliminating annoying buffering delays and interruptions when playing digital media content
- Support Advanced Fast Start, Advanced FF/RW, and Play While Archiving (for Windows Media Player v10 or above only)
- Support Unicast / Multicast streaming and rollover from multicast to unicast automatically
- Provides simplified, flexible administration with increased reliability, security and scalability
- Support multiple streams failover and redundancy
- Support Internet authentication method (Digest, Kerberos or NTLM, NTFS ACL, Anonymous access
  or IP Address) and Vcast authentication plug-in(s) for integration with 3<sup>rd</sup> parties
- Support traffic management and logging
- Support wireless adaptive streaming with enabled forward error correction (FEC)
- Support redistribution via Vcast Streaming Server, Vcast Network or Content Delivery Network (CDN) model using Vcast CDN add-on module (optional)

www.vcast.net Page 1 of 4



## **Vcast (Asia) Limited**

Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899

Fax: (852) 2121-8898 E-mail: enquiry@vcast.net Homepage: http://www.vcast.net

# Mandatory Requirements

VIDEO SESTED SEG PROV	veina
Video search and brov	<del>-</del>
General features:	Each video clip should contains at least the following information in
	their profile:
	- Title
	- Description
	- Keywords
	- Author
	- Copyright
	- Bandwidth
	- Duration
	- File size
	<ul> <li>Video duration can be auto-detected by the VCM</li> </ul>
	<ul> <li>Local Database (Size up to 4GB limit)</li> </ul>
Upload video:	Support at least 100 MB file size or above using web-based
•	interface by HTTP protocol (TCP port 80 or 8080)
	<ul> <li>Progress status bar shows during file upload for the uploading status</li> </ul>
	Video clips will not be published to public until the approval of
	authorized users
Search video:	Support multiple criteria searching of video clips by the fields of
Search video.	video profile including title, description, keywords, author, copyright,
	bandwidth, duration and file size
	Support video preview by unicast on-demand streaming model
	<ul> <li>Support sorting in order for searching results (e.g. by title, duration,</li> </ul>
	etc.)
Delete video:	<ul> <li>Video clips can be selected and deleted by authorized users</li> </ul>
	<ul> <li>Video clips can be deleted in batch mode (i.e. delete multiple video</li> </ul>
	by a simple click)
Channel	
General features:	<ul> <li>Support unlimited* of channels</li> </ul>
	<ul> <li>Support Unicast streaming*</li> </ul>
Create channel:	<ul> <li>Administrator can create channel(s) which contains live or on-</li> </ul>
	demand video streams
Edit channel:	<ul> <li>Information and the scheduled content of the channel can be edited</li> </ul>
	by authorized users
Delete channel:	Channels can be deleted by authorized users
	Chamble can be deleted by damented deere
<b>Encoding Specification</b>	ons
	Video:
	S-Video (4-pin mini-DIN)
	· · ·
Live Innut Course	Composite Video (RCA)  Audio:
Live Input Source:	Audio:
	Aux Stereo (Mini-jack)
	<ul> <li>Line / Mic Stereo (Mini-jack)</li> </ul>
	Camera Mic Mono (Mini-jack)
	<ul> <li>AVI, MP3, MPEG1, MPEG2-PS, MPEG2-TS, MP4, Windows</li> </ul>
Media File Input	Media, Real Media v9,10 (rm), Real Media v9,10 (rmvb), Flash
Source:	VP6, Flash H.264, Quicktime-3GPP2, Quicktime-3GPP,
<del></del>	Quicktime-iPod, Quicktime-iTune and Quicktime-Sorenson
Live and Arabina	·
Live and Archive	Windows Media 6, 7, 8, 9 and SMPTE VC-1  (Phys. City and in the model in this s.)
Streaming Output	(Plus Silverlight publishing)
Format:	Real, Real Helix 9, 10

• Up to 20Mbps@30fps (S-video / Composite)

• Internal video/audio multiplexing

1 independent video stream in multiple bit-rates or format

**Encoding Bit-rate &** 

**Concurrent Streams:** 

Frame Rate

www.vcast.net Page 2 of 4





Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899

Fax: (852) 2121-8898
E-mail: enquiry@vcast.net
Homepage: http://www.vcast.net

	Mandatory Requirements
	Up to 50 live streaming connections output
Capture Format:	Motion JPEG Compressed Video
Capture Format.	<ul> <li>Uncompressed Video (YUV4:2:2, YUV4:2:0, or RGB)</li> </ul>
Supported Live Input Source Resolution &	<ul> <li>Up to 640x480 30 fps (NTSC) or 704x576 25 fps (PAL) of S-video / Composite</li> </ul>
Frame Rates:	

Streaming Specification	ns
Supported Streaming Protocol & Broadcasting Method:	<ul> <li>RTSP, HTTP</li> <li>Unicast, Multicast (Support Rollover to Unicast)</li> <li>Streaming Cache and Proxy</li> <li>Wireless adaptive streaming</li> <li>Re-broadcast from Vcast Streaming Servers or Vcast Streaming Encoders</li> <li>Optional Add-on Module:</li> <li>Vcast CDN (Content Delivery Network)</li> </ul>
Max. Concurrent Streams: Support Broadcasting Channel:	<ul> <li>500 live concurrent streams for up to 150Mbps throughput</li> <li>150 on-demand streams for up to 50Mbps throughput</li> <li>Unlimited*</li> </ul>
Support Streaming Format:	Windows Media 6, 7, 8, 9, SMPTE VC-1 and MP3
Advanced Streaming Technology:	<ul> <li>Fast Start, Fast Cache, Fast Recovery, Fast Reconnect, Instant- on/Always-on, Advanced Fast Start, Advanced FF/RW and Play While Archiving</li> </ul>
Security Authentication	<ul> <li>Digest, Kerberos or NTLM, NTFS ACL, Anonymous access or IP Address</li> <li>Vcast authentication plug-in(s) for integration with 3<sup>rd</sup> parties</li> </ul>
Failover and Redundancy	<ul> <li>Support multiple sources from Vcast Streaming Encoder and switch over automatically</li> <li>Support resilience and failover</li> </ul>
Activity Logging and Reporting	<ul><li>Support Unicode or ANSI characters</li><li>Support specified logging cycle period</li></ul>
Bandwidth and Traffic Management	<ul> <li>Player connections</li> <li>Outgoing distribution connections</li> <li>Aggregate player bandwidth</li> <li>Aggregate outgoing distribution bandwidth</li> <li>Bandwidth per stream per player</li> <li>Bandwidth per outgoing distribution stream</li> <li>Connection rate</li> <li>Player timeout inactivity</li> <li>Connection acknowledgement</li> <li>Incoming bandwidth</li> <li>Fast Start bandwidth per player</li> </ul>
	Fast Cache content delivery rate

Hardware Specifications	
Processor:	<ul> <li>Dual Core Intel® Core2Duo E8500 or above</li> </ul>
Memory:	<ul> <li>1 x 2GB Unbuffered DDR2 ECC RAM</li> </ul>
Video Input Interface:	<ul> <li>1 x S-Video (4-pin mini-DIN)</li> </ul>
	<ul> <li>1 x Composite Video (RCA)</li> </ul>
Audio Input Interface:	1 x Aux Stereo (Mini-jack)
	<ul> <li>1 x Line / Mic Stereo (Mini-jack)</li> </ul>
	<ul> <li>1 x Camera Mic Mono (Mini-jack)</li> </ul>

www.vcast.net Page 3 of 4



## **Vcast (Asia) Limited**

Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899 Fax: (852) 2121-8898

E-mail: enquiry@vcast.net
Homepage: http://www.vcast.net

	Main Storage: • 2 x 500GB SATA2 HDD (RAID 1)
	· ,
Storage Capacity:	<ul> <li>Optical Drive (DVD+/-DL, DVD+/-RW, DVD+/-R, DVD-RAM, CD-ROM, CD-RW)</li> </ul>
	Optional Upgrades:
	External USB Floppy Disk Drive
Network Interface:	<ul> <li>2 x 10/100/1000Mbps Ethernet (RJ45, Copper)</li> </ul>
Power Input Voltage:	<ul> <li>115 VAC (90 to 132 VAC related input) or 230 VAC (180 to 264</li> </ul>
rower input voltage.	VAC related input)
Output Power:	• 510W
Keyboard & Mouse:	Wired keyboard and mouse
Chassis Enclosure and	3U 19' inch rack-mountable chassis
Dimension:	660 x 430 x 132 (D x W x H) mm
	<ul> <li>Microsoft® Windows Server 2003 Enterprise Edition (32bits)</li> </ul>
	<ul> <li>Microsoft® Windows Media Services 9</li> </ul>
Preinstalled OS &	<ul> <li>Microsoft® Windows Media Encoder 9</li> </ul>
Software:	<ul> <li>Microsoft® Windows Media Player 11</li> </ul>
Software.	<ul> <li>Microsoft® SQL Server 2008 Expression Edition</li> </ul>
	<ul> <li>Vcast Content Management (VCM) Lite Version</li> </ul>
	<ul> <li>Remote control tools for remote administration via TCP/IP</li> </ul>

www.vcast.net Page 4 of 4