

Mandatory Requirements

VCAST Streaming Server 5800R-WM (VC-SR5800R-WM)

General Features:

- Support high-quality video/audio broadcast at various bit-rates for multiple devices (PC, TV via VBOX or Windows Mobile)
- Support live and on-demand video / audio broadcasting via any TCP/IP networks
- Highly scalable and expandable from small to large scale of streaming
- Ease of support and maintenance with remote management
- Support latest streaming technologies for best user experience over Internet, Intranet or Wireless
- Reliable for 7/24 operation with high availability and backup options
- Support publishing, re-broadcasting and content delivery via Vcast Network for global broadcasting (optional at charge-basis)
- Fully compatible and managed by Vcast Content Management System
- Provided by Certified Windows Media Hardware Product Vendor (Integrated Capture/Encoding Solutions and Appliances) listed in
- <u>http://www.microsoft.com/windows/windowsmedia/service_provider/Hardware/default.aspx#capture</u>
 Provided by Certified Windows Media Software Product Vendor (Software/Content Management) listed in

http://www.microsoft.com/windows/windowsmedia/service_provider/Software/default.aspx#content

Streaming Features:

- Support and compatible with Windows Media 6, 7, 8, 9, SMPTE VC-1, MP3 formats
- Support unlimited* no. of broadcasting channels
- Support "Fast Streaming" capabilities which can effectively eliminate buffering time, and reduce the playback interruptions due to network conditions. Features like Fast Start, Fast Cache, Fast Recovery, and Fast Reconnect provide an always-on viewing experience by streaming content with minimal buffering and down-time, even over high latency network connections such as wireless and satellite.
- Support instant-on/always-on playback which can dramatically improves streaming reliability, responsiveness user experience and virtually eliminating annoying buffering delays and interruptions when playing digital media content
- Support Advanced Fast Start (for Windows Media Player v10 or above only)
- Support Unicast streaming
- Provides simplified, flexible administration with increased reliability, security and scalability
- Support multiple streams failover and redundancy
- Support Internet authentication method (Digest, Kerberos or NTLM, NTFS ACL, Anonymous access or IP Address)
- Support traffic management and logging
- Support wireless adaptive streaming with enabled forward error correction (FEC)
- Support redistribution via Vcast Streaming Server, Vcast Network or Content Delivery Network (CDN) model using Vcast CDN add-on module (optional)

VCAST Content Management (VCM) Lite Features:

Video search and brow	sing
General features:	 Each video clip should contains at least the following information in
	their profile:
	- Title
	- Description
	- Keywords
	- Author
	- Copyright
	- Bandwidth
	- Duration
	- File size
	 Video duration can be auto-detected by the VCM
	Local Database (Size up to 4GB limit)

Vcast (Asia) Limited



Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899 Fax: (852) 2121-8898 E-mail: <u>enquiry@vcast.net</u> Homepage: <u>http://www.vcast.net</u>

	Mandatory Requirements
Upload video:	 Support at least 100 MB file size or above using web-based interface by HTTP protocol (TCP port 80 or 8080) Progress status bar shows during file upload for the uploading status Video clips will not be published to public until the approval of
Search video:	 authorized users Support multiple criteria searching of video clips by the fields of video profile including title, description, keywords, author, copyright,
	 bandwidth, duration and file size Support video preview by unicast on-demand streaming model Support sorting in order for searching results (e.g. by title, duration, etc.)
Delete video:	 Video clips can be selected and deleted by authorized users Video clips can be deleted in batch mode (i.e. delete multiple video by a simple click)
Channel	
General features:	Support unlimited* of channelsSupport Unicast streaming*
Create channel:	 Administrator can create channel(s) which contains live or on- demand video streams
Edit channel:	 Information and the scheduled content of the channel can be edited by authorized users
Delete channel:	Channels can be deleted by authorized users
Strooming Creationtic	
Streaming Specificatio	• RTSP, HTTP
Supported Streaming Protocol & Broadcasting Method:	 Unicast Streaming Cache and Proxy Wireless adaptive streaming Re-broadcast from Vcast Streaming Servers or Vcast Streaming Encoders Optional Add-on Module:
Max. Concurrent Streams:	 Vcast CDN (Content Delivery Network) 2,000 live concurrent streams for up to 600Mbps throughput 500-1000 on-demand streams for up to 200Mbps throughput
Support Broadcasting Channel:	 Unlimited*
Support Streaming Format:	• Windows Media 6, 7, 8, 9, SMPTE VC-1 and MP3
Advanced Streaming Technology:	Fast Start, Fast Cache, Fast Recovery, Fast Reconnect, Instant- on/Always-on and Advanced Fast Start
Security Authentication	Digest, Kerberos or NTLM, NTFS ACL, Anonymous access or IP Address
Failover and Redundancy	 Support multiple sources from Vcast Streaming Encoder and switch over automatically Support resilience and failover
Activity Logging and Reporting	Support Unicode or ANSI charactersSupport specified logging cycle period
Bandwidth and Traffic Management	 Player connections Outgoing distribution connections Aggregate player bandwidth Aggregate outgoing distribution bandwidth Bandwidth per stream per player Bandwidth per outgoing distribution stream Connection rate
	Player timeout inactivity

Vcast (Asia) Limited



Unit 109-110, No. 5 Science Park West Avenue Hong Kong Science Park, Shatin, N.T., Hong Kong Tel: (852) 2121-8899 Fax: (852) 2121-8898 E-mail: <u>enquiry@vcast.net</u> Homepage: <u>http://www.vcast.net</u>

-	Connection acknowledgement
	Incoming bandwidth
	Fast Start bandwidth per player
	Fast Cache content delivery rate
Hardware Specification	S
Processor:	Quad Core Intel® XEON E5405A or above
Memory:	 2 x 1GB ECC Fully Buffered DDR2 RAM
Storage Capacity: Network Interface: Power Input Voltage:	 Main Storage: 5 x 146GB SAS hot-plug HDD in RAID 5 Configurable to support H/W RAID 0, 1,1E, 5, 5EE, 6, 10, 50, 60, JBOD Optical Drive (DVD+/-DL, DVD+/-RW, DVD+/-R, DVD-RAM, CD-ROM, CD-RW) Optional Upgrades: External USB Floppy Disk Drive 2 x 10/100/1000Mbps Ethernet (RJ45, Copper) 115 VAC (90 to 132 VAC related input) or 230 VAC (180 to 264 VAC related input)
Output Power:	 2+1 650W hot-swap redundant power supply
Keyboard & Mouse:	Wired keyboard and mouse
Chassis Enclosure and Dimension:	 3U 19' inch rack-mountable chassis 660 x 430 x 132 (D x W x H) mm
Preinstalled OS & Software:	 Microsoft® Windows Server 2008 Standard Edition (64 bits) Microsoft® Windows Media Services 9.5 Microsoft® Windows Media Player 11 Remote control tools for remote administration via TCP/IP

* Limited by the hardware capability